



ULTRA™ - 2500

25oz PVC Coated Vinyl

| SPECIFICATIONS | | TEST METHOD |
|---------------------------------|------------------------------------|---|
| Composition | 1100Dtex *1100Dtex 9*9/cm blackout | DIN 53830/DIN60001 |
| | 1000D *1000D 23x23/inch | ASTM D 751 |
| Weight | 850 gsm +/- 20gsm | DIN53352 |
| | 25oz | ASTM D 751 |
| Laquering | 1/1 Acrylic | |
| Surface Finish | Glossy | |
| Color | White | |
| Breaking Strength (weft x warp) | 2800/2500 N/5cm | DIN 53354 |
| | 636/568lbs/2" | FS 5100 |
| Tearing Strength (weft x warp) | 400/350 N | DIN 53363 |
| | 90/79lbs | FS 5100 |
| Adhesion Strength | 100N/5cm | DIN 53357 |
| | 22lbs/2" | FS 5970 |
| Width | 1000 ~ 3200mm | |
| Fire Resistance | 61" & 98.5" B1, B2, NFPA-701 | *additional widths available upon request |
| Temperature Resistance | -30°C ~ 70°C | DIN 53372 |
| | -20°F ~ 158°F | FS 5874 |

sales@kedersolutions.com

(888) 727-7050 | Fax (888) 727-7060

www.KederSolutions.com

