



14 oz. Hybrid-Coated Tent Fabric

FEATURES:

- Good tensile and tear strength
- Good availability on anti-UV, moldproofing, antiabrasion
 - Good stretch ability and softness
- Good flexibility and anti-folding strength thanks to extra coating
 - Good anti-dirt thanks to two-side glossy finish

APPLICATIONS:

-Ideal for short-term and medium-term mobile connections

SPECIFICATIONS		TEST METHOD
Composition	1100Dtex *1100Dtex 3.5/cm blackout 1000D*1000D 9*9/inch blackout	DIN 53830/DIN60001 ASTM D 751
Weight	480gsm +/- 20gsm 14oz	DIN53352 ASTM D751
Lacquering	/	
Surface Finish	Glossy	-
Color	White	-
Breaking Strength (Warp x Weft)	1450/1150 N/5cm 326 / 259lbs / 2"	DIN53354 FS 5100
Tearing Strength (Warp x Weft)	400 / 400N 90 / 90lbs	DIN53363 FS 5970
Adhesion Strength	90N/5cm 20.5lbs/2"	DIN53357 ASTM D751
Width	1000~3200mm 36"~126"	-
Fire Resistance	B1, B2, NFPA-701 TM2	
Temperature Resistance	- 20°F ~ -158°F	FS5874

sales@kedersolutions.com

(888) 727-7050 | Fax (888) 727-7060

www.kedersolutions.com