



18 oz. Tarp Vinyl

FEATURES:

- High tensile, tear and good adhesion strength
 - Good flexibility
 - Excellent anti-abrasion

APPLICATIONS:

Ideal for multiple heavy duty application

SPECIFICATIONS		TEST METHOD
Composition	1100Dtex *1100Dtex 3.5/cm warp-knitted 1000D*1000D 9*9/inch warp-knitted	DIN 53830/DIN60001 ASTM D 751
Weight	610gsm +/- 20gsm 18oz	DIN53352 ASTM D751
Lacquering	/	
Surface Finish	Matte or Gloss	-
Color	Yellow or Upon Request	-
Breaking Strength (Warp x Weft)	1400/1150 N/5cm 318 / 250lbs / 2"	DIN53354 ASTM D 751
Tearing Strength (Warp x Weft)	320 / 270N 72 / 60lbs	DIN53363 ASTM D 751
Adhesion Strength	/	DIN53357 ASTM D 751
Width	1000~3200mm 36"~126"	
Fire Resistance	B1, B2, NFPA-701 (Upon request)	
Temperature Resistance	- 30°F ~ 70°F - 20°F ~ 158°F	DIN 53372 FS 5874

sales@kedersolutions.com
 (888) 727-7050 | Fax (888) 727-7060
www.kedersolutions.com